## PT-E550WVP

In addition to the extensive range of TZe tapes in various colours and sizes, special tapes for industrial use have been developed for specific labelling tasks.

Flexible-ID Tape
Use on curved sufaces, sharp bends or cylindrical surfaces.

Strong Adhesive Tape
Use on uneven, rough and textured surfaces.

Heat-shrink tube
Shrinks and grips cable when heat is applied.

Technical Specifications

Hardware

Display Type	16 chrs x 3 lines backlit graphic LCD with Print preview
Interfaces	USB 2.0, Wi-Fi, Wireless Direct
Print Speed	30mm / second (maximum)
Maximum Tape Width	24mm
Maximum Print Height	18mm
Cutter Type	Automatic (Full & Half)
Battery Type	BA-E001 Li-ion rechargeable battery (supplied) 6 x AA alkaline/rechargeable batteries (LR6/HR6 - not supplied)

Label Creation

Dedicated Labelling Functions	General, Faceplate, Patch panel, Punch block, Cable wrap, Cable flag, Heat shrink tube, Serialise (automatic number incrementation)
Fonts	14 fonts, 10 styles, 6 - 48 point size
Maximum Lines per Label	7 (on 24mm width tape cassette)
Maximum text blocks	99
Symbols	384
Frames	7
Barcodes	9 protocols
Automatic numbering	1-99
Copy Printing	1-99
Vertical Text Printing	Yes
Rotated text printing	Rotate once, Rotate and repeat

Memory

Maximum Characters per Label	1500
Label Memory Locations	99

PC Software Main Features

Supported Operating Systems	Windows® Vista, Windows® 7, Windows® 8, Mac OS® X 10.6 or greater
Cable Labelling Wizard	Yes
Font Faces	All installed true-type fonts
Font Styles	12
Image Import	JPG, BMP, TIFF and other Popular types
Screen capture	Yes
Frames	153
Barcodes	21 protocols including 1D/2D barcodes

Included Items

In the Box	PT-E550WVP labeller 24mm Black on Yellow Strong Adhesive tape cassette (8m) 12mm Black on White Flexible ID tape (8m) Li-ion Rechargeable battery AC adapter Label design software and Printer driver CD-ROM USB cable, wrist strap and user guide

Supplies

Tape type /Tape widths	TZe tape cassettes: 3.5, 6, 9, 12, 18, 24mm HSe tube cassettes: 5.8, 8.8, 11.7, 17.7, 23.6mm HGe tape cassettes: 6, 9, 12, 18, 24mm

Optional Accessories

Batteries	BA-E001 Li-ion Rechargeable battery AA alkaline/rechargeable batteries (LR6/HR6)
AC Adapter	AD-ES AC adapter

Weight and Dimensions

	126mm (W) x 250mm (H) x 94mm (D) 1.05kg

brother at your side

www.brother.com.sg

Brother Earth
Working with you for a better environment
www.brotherearth.com

PT-E550WVP

brother at your side

Industrial PC Labeller

Create durable labels for electrical or datacom installations, via easy-to-use built-in labelling functions, PC software or from your smartphone or tablet with Brother Mobile Cable Label App.

• Large backlight graphic display

• Prints 3.5, 6, 9, 12, 18 and 24mm TZe laminated Tapes

• Prints 5.8, 8.8, 11.7, 17.7, 23.6mm Heat shrink tube

• Supports HGe laminated Tapes

• Advanced cutter (including half cutter) for easy-to-peel labels

• Includes 2 tape cassettes, AC adapter, Lithium-ion Battery, USB cable, hand strap and Tough carrying case

LABELS THAT STICK. | P-touch

PT-E550WVP

Ensuring cables, conduits, switches and sockets are clearly identified with long lasting, durable labels is essential for electricians, datacom, telecom and security equipment installers.

Wide variety of Print width
Prints TZe laminated labels from 3.5 to 24mm
HGe laminated labels from 6 to 24mm
Heat Shrink Tube labels from 5.8 to 23.6mm

Large backlit graphic LCD
Easy to view symbols with print preview
of your label before printing.

Sequential numbering
Print labels containing a sequence
of numbers or letters.

384 built-in symbols
Includes common electrical, datacom,
AV, security and safety symbols

Print preview
Preview your labels before print

Special label functions
Easy to create General, Faceplate,
Cable flag/wrap, Patch panel and
Punch down block labels

Database search/merge/print
Upload data from your PC to print
labels on-site

USB & Wi-Fi
Print from PC or mobile wirelessly

P-touch laminated labels – designed to last

Brother P-touch laminated TZe tapes are available in many different colours and sizes. The thermal transfer ink is sandwiched between two protective layers of PET (polyester film), protecting the text against the effects of liquids, abrasion, temperature, chemicals and sunlight. As the labels have been tested to the extreme, you can be confident of a Professional quality label that has been designed to last.

P-touch LABELS
TESTED
TO THE EXTREME

| Water Resistant | Temperature Resistant | Abrasion Resistant | Fade Resistant | Chemical Resistant | Laminated | Easy Peel | Strong Adhesion |